

1080P monitors

SKU:

EAN:



FEATUES

The Edis 1080P monitors 178° wide field of view Wonderful vision, full view IPS wide-angle hard screen, up to 178° viewable range, color at every angle is transparent and true. Whether it is business office or daily life, the wonderful and clear vision will be presented in your eyes.Reduces visual Fatigue Flicker Safe reduces the onscreen flicker level to almost zero, which helps protect your eyes. User can comfortably work throughout the day.Color Calibrated Helps maintain accurate color on the screen and prevent gradual changes.Pleasant low blue light Comfortable and eye protection, The low blue light mode can filter short-wave blue light that damages eyesight, Reduce your visual pressure and make work easier.



MONITORS

Panel size	19	21.5"	23.6/23.8
SKU	0200158	0200159	0200160
Panel type	TFT-LCD	TFT-LCD	TFT-LCD
Backlight type	ELED	ELED	ELED
Panel manufacturer			
Panel technology	IPS	IPS	IPS
View angle	178/178	178/178	178/178
Max. Resolution	1920×1080	1920×1080	1920×1080
Aspect Ratio (H:V)	16: 9	16: 9	16: 9
Refresh rate(Hz)	75Hz	75Hz	75Hz
Brightness	220cd/m ² (±20%)	220cd/m ² (±20%)	220cd/m ² (±20%)
Surface treatment	Hard Coating (3H)	Hard Coating (3H)	Hard Coating (3H)
Contrast Ratio	4000:1 (Typ.) (Transmission)	4000:1 (Typ.) (Transmission)	3000:1 (Typ.) (Transmission)
Point spacing	0.08275×0.24825 mm	0.08275×0.24825 mm	0.0915×0.2745mm (H×V)
Pixel pitch	0.24825×0.24825 mm	0.24825×0.24825 mm	0.2745×0.2745mm (H×V)
Color quantity	16.7M (8-bit)	16.7M (8-bit)	16.7M (8-bit)
Color gamut	95% sRGB	95% sRGB	96% sRGB
Display mode	Normally Black	Normally Black	Normally Black
Speakers	1Wx2	1Wx2	1Wx2
Pixel arrangement	RGB vertical stripe	RGB vertical stripe	RGB vertical stripe
Response time	5ms (OD)	5ms (OD)	5ms (OD)
Dynamic Contrast Ratio (DCR)	1,000,000: 1	1,000,000: 1	1,000,000: 1

OTHER FEATURES

Game plus	YES	YES	YES
HDR function	YES	YES	YES
VESA			

INPUT/OUTPUT INTERFACE

HDMI input	x1	x1	x1
VGA input	x1	x1	x1
Headphone Output	x1	x1	x1

POWER

Power supply mode	External power supply	External power supply	External power supply
AC input	100-240V,50/60Hz,1.0A	100-240V,50/60Hz,1.0A	100-240V,50/60Hz,1.0A
DC input	12V-2.5A	12V-2.5A	12V-2.5A
Power Consumption	< 25W	< 25W	< 25W
Stand by Mode	0.16	0.16	0.16
Off Mode	0.16	0.16	0.16

ACCESSORY

HDMI signal line	x1	x1	x1
Power line	x1	x1	x1
Manual	x1	x1	x1
Power Consumption	< 25W	< 25W	< 25W
Qualified Certificate	x1	x1	x1
power adapter	x1	x1	x1