

# C68 Controller

SKU: 0200167



## FEATUES

The Edis C68 Controller Ergonomic design, comfortable to use. Compatible with multi-clock control protocols: Pelco P, Pelco D, VISCA, DAHUA, HIKVISION, etc. Communication distance RS485, RS422 up to 1.2km, LCD screen, backlight, displays command menu, control protocol name, current camera address, output display address, rocker status. The 3 d control rocker, controls the speed of the head and lens factor multiplication; the 2 d rocker controls the speed of the head, supporting all functions of the shortcut key operations. Built in control protocols Pelco\_P, Pelco\_D, VIDO\_B02, baud rate is optional.



## ELECTRICAL SOURCE

Voltage	9 v to 12 v AC/DC
Power	5 w

## ENVIRONMENT

Ambient temperature	0 ° C to +50 ° C
Relative humidity	0 ~ 95%(no cold doubt)

## COMMUNICATION INTERFACE

Connection type	six-bit plug, RJ45 interface
Port type	RS485/422
Communication rate	2400/4800/9600/19200 BPS
Maximum transmission distance	1200 m (0.5mm twisted-pair)

## CONTENT MANAGEMENT

Dimensions	218*180*98 mm
Net weight	0.7 kg
Gross weight	1.2 kg