

# Conference Soundbar with 3x desktop mics

SKU: 2001005

## FEATUES

The Edis Conference Soundbar with 3x desktop mics Built-in 2\*4W speakerphone, 5.8G Wireless or USB 2.0 connection optional. Using world-class echo cancellation technology, noise cancellation technology, howling suppression technology, and dynamic noise suppression technology, you can clearly output meeting content although in a noisy environment. Speakerphone standby time up to 6 months, working time up to 4.5 hours. Equipped with 12V 1A fast charge. Omni-directional microphone standby time up to 3 months, working time up to 4 hours. Equipped with 12V 1A fast charge. Small size for easy movement, USB Plug & Play. It's easy to use by abandoning traditional complex connection method.



## DIMENSIONS

Conference Speakerphone with expansion Microphones

Built-in Audio	
Built-in Digital silicon Microphone	
Type	Digital silicon Microphone
Sensitivity	Built-in Microphone: -22dBFS
SNR	60dB
Frequency response	100Hz – 16kHz
Echo Cancellation	world-class Echo cancellation technology, echo cancellation time up to 256ms
Noise Cancellation	>12dB
Sampling frequency	Record: 16kHz / Playback: 48kHz
Voice pick up range	3M
Transmission Model	Wired, USB2.0 (Between all-in-one device and PC) Wireless, 2.4G (Between all-in-one device and Microphone)
Speaker power	Double Channels 4Wx 2

## TECHNICAL SPECIFICATIONS

Expansion Microphone

(Maximum can connect 3 expansion Microphone)

Type	Digital silicon Microphone
Sensitivity	-26dBFS @1kHz 1Pa
SN	59dB
Frequency response	100Hz – 16kHz
Sampling frequency	Record: 48kHz
Voice pick up range	3M
Wireless transmit power	2.4G: +5dBm
Microphone power	0.2W MAX
Charge Jack	USB type-C /Charging board contact charging
Control Mode	Touch button control
Button function	ON/OFF, Microphone Mute
Status Display	Two-color LED indicator

All-in-one Device Power	9W MAX
Control Mode	Touch button control /remote control
Button function	ON/OFF( Battery Check)、Volume+、 volume-、speaker Mute、Microphone Mute、Scene switch
Remote function	Audio: Volume+、Volume-、 microphone mute、speaker Mute,ON/OFF Video: ZOOM+、ZOOM-、 up/down/left/right movement、OSD Menu
Status Display	Two-color LED indicator
Power adapter	DC12V±0.2V,1A
Working temperature	-10℃ ~ 40℃
Environment humidity	0-95% RH
length*width*height	400mm×61mm×70mm
Weight	950g

Power adapter	Charging boardDC5V±0.2V,2A
Battery	800MAH
Standby time	6 month
Work time	>8hours
Working temperature	-10 – 40℃
Environment humidity	0-95% RH
length*width*height	φ70x49mm
Weight	300g

## PACKAGE CONTENTS

- 1x Conference speakerphone
- 1x RF5.8 USB Dongle
- 1x charge plate
- 1x USB type-C cable
- Expansion microphones 1-3 (optional)
- 1x Manual