

EA39-3C Ceiling Microphone with reinforcement AI



SKU: 0110039-3C

EAN:

FEATUES

The Edis EA39-3C Ceiling Microphone with reinforcement AI Built-in powerful audio processing unit, ultra-low signal processing delay; Adaptive fast convergence algorithm,voice intelligent tracking, intelligent noise reduction,echo cancellation, automatic gain, de-reverberation and other advanced technologies, double-talk without suppression, you can easily listen in noisy environments.For ordinary users, there is no need for professional tuning,and it can be used for regular conference applications when it is turned on. For enthusiast users, you can also open the EQ interface and enter the professional tuner mode for personalized high-end tuning.Standard Interface; Plug and Play, Equipped with standard USB2.0 and Aux audio interfaces,the device is plug and play, and can meet the dual-mode application of digital and analog audio.



EA39-3C

Microphone Type	Digital Array Microphone
Microphone Array	Built-in 6 mics to form a circular array microphone
Pickup Range	3m
Sensitivity	-38 dBFS
Signal Noise to Ratio	64 dB(A)
Frequency Response	50Hz - 16kHz
Automatic Echo Cancellation (AEC)	Support
Automatic Noise Suppression (ANS)	Support
Automatic Gain Control (AGC)	Support

HARDWARE INTERFACES

Network Interface	down cascade network interface
USB Interface	1 x 3.5mm Spk-out Interface USB audio interface (Type-C),support UAC1.0 protocol, audio data communication, software upgrade and parameter configuration
USB Interface	AUX1 , AUX2 line audio input and output