

# EC102 USB Speaker Phone

SKU: 0200102



## FEATUES

The Edis EC102 is a Easy to carry, small and medium-sized meetings will be launched at any time.Acoustic IntelliSense™ .HD, full duplex audio solution.Microphone dynamic speech enhancement technology.Adaptive high-definition amplification technology.Low power consumption design,The 3.5mm interface can be used for docking mobile phones or other analog devices.Support USB.360 degree omnidirectional pickup, plug and play.The inductive button design is more waterproof, more dust-proof and more durable.Enable customizable development.



## MICROPHONE

|                    |                 |
|--------------------|-----------------|
| Distance           | 6m              |
| Frequency response | 50-169kHz       |
| Directivity        | Omnidirectional |

## PACKING

|                      |   |
|----------------------|---|
| Telephone size (RxH) | 75mm x 30mm   |
| weight               | 0.31kg  |
| Packing catalogue    | Quick User Gudie USB Cable,Omnidirectional microphone |

## MEETING CAPACITY

|                        |                      |
|------------------------|----------------------|
| Covering area          | 15-30 m <sup>2</sup> |
| Number of participants | 6-12 person          |

## REPRODUCER

|                    |          |
|--------------------|----------|
| Frequency response | 20-20kHz |
| Volume             | 85dBA    |

## AUDIO FREQUENCY

|                               |         |
|-------------------------------|---------|
| Full duplex echo cancellation | support |
| Noise suppression             | support |
| Gain control                  | support |
| Echo tail lengyh              | 300ms   |

## CONNECTION MODE

|         |   |
|---------|---|
| Network | 1xUSB Data Communication<br>1x3.5mm audio interface |
| Key     | Induction button                                    |

## ENVIRONMENT CONDITION

|                      |                          |
|----------------------|--------------------------|
| Power supply         | USB:5V DC@450mA(Maximum) |
| Rechargeable battery | NA                       |
| Storage temperature  | -22-131°F(-30°-55°C)     |
| Relative humidity    | 20-85%(non-condensing)   |

|                     |                         |
|---------------------|-------------------------|
| Support operation   | windows XP/Vista/7/8/10 |
| Working temperature | 32-104°F(0-40°C)        |
| Authentication      |                         |