

EC192 USB Wireless Dongle



SKU:

FEATUES

The Edis EC192 USB Wireless Dongle is One - button screen, plug and play.USB port, no permission no software installation needed, convenient and fast. Business, office, wireless conference, meeting without extension cord, fast projection screen easy connection, office presentation more funny and efficient.No driver, compatible with multiple devices, support mobile phone/tablet/computer wireless projection screen to large screen or projector.HD screen display, shows rich details, more layers of color, brings a more realistic, more natural visual experience.Support Multiple Protocols.USB Display/Miracast/Airplay/DLNA , it casts smart devices (phone,PC,Pad) to TV/Projector via WiFi.Compatible with Windows/Mac/Android/iOS platforms Support mobile phones,notebooks,desktop computers Laptops,tablets and many other devices for mirroring.Home Theater Better Atmosphere, Enjoy giant-screen film and no need go to cinema.A good assistant for meeting.Big screen makes the meeting more efficient.Big Screen Era.High-definition large-screen experience the maximum support 1920*1080P Resolution.



WINDOWS MIRRORING VIA SOFTWARE

Installation	Keep PC and box at the same internet, No need installation
Support System	Windows 7/8/10
Resolution	1920*1080、1280*720、720*480
Frame Rate	30~60Frame
Delay time	90~180ms
Display mode	Support extended screen
Connection paths number	1~8
The Max qty display screen	Single Screen

SPECIFICATION

iPhone	iOS8 above, AirPlay mirroring, support multi-screens
Andorid	Android 5.1 above, USB Display App(scan QR to download APP)
Video Decoder	H.265,H.264,VP8,RV,WMV,AVS, H.263,MPEG4 etc
Audio Decoder	MP3,WMA,AAC,WAV,OGG,REAL etc
Image Format	JPEG,BMP,GIF,PNG,TIFF etc
Transmission Protocol	WiFi,DLNA,Miracast Protocol,Airplay etc

OPERATION SYSTEM

System version	Linux 3.10
CPU	ARM Cortex A7 x2
HDMI output	1
DDR	512M DDR3
Flash Memory	32M
Wired Networking	yes

OTHERS

Resolution	Max 1920x1080 60Hz
Input	DC:5V
Max consumption	5W
Size (L*H*W)	59mm
Power adaptor*1	HDMI cable*1
Date cable*1	USB button: >=1

Soft AP	802.11AC 5.8G
Wi-Fi	5.8G

Environment	10°C~40°C(working temperature); 10%~90%(working humidity)
-------------	--

WIRELESS USB DONGLE

Installation	No installation, no configuration
Connection	USB Device
Support system	Windows 7/8/10,Apple Mac
Resolution	480P~1080P
Frame Rate	30~60Frame
Delay time	90~180ms
Transmit distance	No obstacle around 30m

Display mode	Support extend screen (Windows 7/8/10)
Connection number	1~8 tx (If above8 tx, need additional routers)
The Max qty display screen	Single screen
Wireless Speed	TX 300Mbps
Wireless Protocol	IEEE 802.11 a/g/n/ac
Channel	5.8G
Authentication Protocols	WPA2-PSK