

Wall/Ceiling mount LCD Display

SKU: 0030032

EAN:



FEATUES

- Wall or ceiling mounted 1080P HD displays original color, 1920*1080 HD resolution and 700 nits brightness with built-in Android media player.
- WiFi connection
Remote real-time advertising with WiFi connecting to remote CMS server or local PC, tablet or mobile phone, includes CMS software for locally uploading media from USB disk, Mobile phone or TF card.
- Split screen capability
Split screen enables several picture to be shown, switches between horizontal or vertical making content multicast more efficient.
- Display Interface Multiple displays
Multi-function advertising from remote server, automatic rotation loop play providing advertising diversification. Sequencing for time and date, product price, intelligent split screen, picture rotation, subtitles, video playback, music playback, logo, etc.
- Automatic playback supports a variety of file formats : MP4, AVI, DIVA, XVID, VOB, DAT, MPG, RM, RMVB, MKB, MOV, HDMOV, M4V, PMP, AVC, FLV; Support music format: MP3, WMA, OGG, AAC, AC, DTS, FLAC, APE;



SPECIFICATION

Size(in ch)	15.6	18.5	21.5	23.6	27	32	43	49	55	65	75	86	98
Install	Wall mounted/Ceiling							Wall mounted/Ceiling Floor stand					
Stand	RK3188 1+8G,BOE original module with content publish software							RK3188 1+8G,BOE original module with content publish software					
CPU													

SPECIFICATION

Specification

Panel

Dimension	LCD screen
Capacitive touch screen	10 points touch screen (Capacitive /infrared)
Writing method	Finger or stylus
Screen scale/Display area	Depends on different size
Display color	16.7M
Visual angle	H: 178° V: 178°

Brightness	350 cd/m2
Contrast	1300:1
Response time	5ms
Screen Life(hrs)	> 50,000(hrs)
Configurati on	
CPU	RK3288
Memory	2G DDR3
Storage	8GB Normally, can be extended up to 32GB
OSD language	Multi language support
System	Android 7.1
Network	
Ethernet	10M/100M
WiFi	802.11 b/g/n
Bluetooth	Support V2.1+EDR/BT v3.0/BT v3.0+HS/BT v4.0
Interface	
USB Port	USB 2.0
RJ45	10M/100M
TF Card	Push-push type TF socket, support at most 32GB TF card
Multi-Media	
Video	Support MPEG-1, MPEG-2, MPEG-4,H.263, H.264, RV, etc.
Audio	Support MP4, WMA, AAC and so on
Picture	JPEG, PNG, BMP and so on
Other parameters	
The input voltage	AC100-240v 50/60HZ
Standby power	≤1W, support low power standby mode
Material	Metal case
Speaker	2×6W speakers (8Ω)
Color	Black Normally, OEM support
Installation	Wall mounted/Ceiling / floor standing
Operating temperature/humidity	0℃~50℃/20% ~ 80%
Store temperature/humidity	-10℃~60℃/5--95%
Software support	Free installation applications (maps, games,e-mail, self developing apps, etc.)
Attachment	
Adapter	One
Warranty card	One
Qualification certificate	One
User's Manual	One
Screw and Key	One
Antenna	One