

Wireless Central Controller Unit



SKU:

FEATUES

- Support Meeting Mode: Limit(1/2/3/4), FIFO (1/2/3/4),Chairman Only,
- Support up to 999 units microphones with one YCU892M,5 microphones can be turned on at the same time.
- 8 hours during speech or approx. 30 hours when standby.
- Adopt multi-channel high band and intermediate band frequency selective filtering, fully eliminate interference signal
- Anti-interference from cellphone
- Operation distance up to 100 meters
- Support video camera auto-track



SPECIFICATIONS

Audio channel

Transmission method	UHF Wireless (one way)
Audio channel	5(1 chairman,4 delegate)
Carrier frequency band	500MHz~950MHz
Modulation method	FM
Receiving sensitivity	-100dBm
Audio gain	≤20
Frequency response	50Hz-15KHz
S/N Ratio	>85dB
T.H.D.	<0.8%

Data control channel

Transmission method	Wireless (two-way)
Data channel	16
Frequency Range	422.4MHz~438.4MHz
Modulation method	FSK
Receiving sensitivity	-100dBm
Transmission consumption	≤6dBm
Communication rate	100KBPS
Frequency deviation	<0.002

System

Power supply	DC12~15V≤1A
Signal covering range	Radius 60 meters
Consumption Rating	7W
Operating temperature range	-10-40 degree
Dimensions	485*355*85mm
N.W	7kg